

## TECHNICAL SPECIFICATIONS

### Full Color Laser Projector PHAENON AT RGB 10W

Exclusively Based on Coherent® Genesis  
TAIPAN Laser Sources



Front View

#### Laser

Class	4				
Type	CW, analog modulated				
Beam diameter (1/e <sup>2</sup> )	1.4mm				
Beam divergence (1/e <sup>2</sup> ) Full angle	< 1.5mrad				
<b>Laser source</b>	<b>Wave-length</b>	<b>Power spec.</b>	<b>Power max.</b>	<b>Power D65 white</b>	<b>Remark</b>
Red	639nm	2W	2 – 3W	2W	
Green	530nm	3W	3 – 4W	1.3W	Green surplus
Blue	460nm	1W	1 – 2.5W	1W	
Total output power	6W	9.5W	<b>4.3W</b>		
Brightness	<b>1040 lm</b>				
Characteristic	Well balanced system with acceptable green surplus. Polarized i.e. can be "Tandemized"				

#### Projector

Scanner	CTI 6210 / 6800H with Turboscan driver
Aperture	3mm
Projection angle horizontal	80° maximum / 50° typical
Projection angle vertical	80° maximum / 50° typical
Response time (2°opt. step)	0.2ms
Laser emission window	B+W antireflective coated
Built-in Options	
Grating module	Two Effect wheels: 1. With grid grating 1 (Grid WT), ultra fine line grating (Machado), special grid (Stargate) 2. With grid grating 2 (Grid XT), line grating, Lumia
"compact Mark 2"	Laser show controller

#### Safety Features

Key switch, Interlock loop. Emission LED
Scan fail safety
Multiple control loops with shutdown at malfunction
External mechanical beam stop

## TECHNICAL SPECIFICATIONS

### Full Color Laser Projector PHAENON AT RGB 10W

Rear View



#### Connections

AC power input	Air tight chassis connector PowerCon® 3-pole
Projector signal, analog	ILDA In, ILDA Out, D-sub 25
Remote control	7pin XLR (RS232, external key switch, Interlock)
DMX In/Out (optional)	5pin XLR Jack
LAN (optional)	8pin RJ45 Jack

#### Electrical

AC power input	100-120VAC / 200-240VAC / 50-60Hz auto ranging, switch mode
Input power	750W maximum

#### Thermal

Max. ambient temperature	50°C
Min. ambient temperature	-5°C
Protective housing	IP 54
Cooling	Forced air, low noise regulated fans

#### Physical

Size (L x W x H)	640 x 400 x 200mm
Height with yoke	approx. 330mm
Width with yoke	approx. 480mm
Weight	approx. 28kg (without yoke, without options)
Material	Aluminum anodized, black
Construction	Dust proof housing

#### Conformity

CE, CDRH compliant / variance

Technical specifications subject to change without prior notice!